

INTUS 3460

- + MagicEye for direct signaling
- + Customized keyboard design
- + Flexible touch screen or robust membrane keyboard
- + Integrated security package with firewall, data encryption and password



Data acquisition terminal for time and attendance recording, access control, and for use as an employee information station. The INTUS 3460 is not only a repeated design-award winner. The integrated security package ensures highest data integrity with embedded firewall, data encryption to the host and the connected access readers, and a three-tier hierarchical password concept. Excellent functional ergonomics is provided by the MagicEye which allows swift and secure optical signaling to passing users.



Technical Data	INTUS 3460 time	INTUS 3460 timeplus	INTUS 3460 plus
Memory 1MB / optionally expandable to 3MB / 5 MB	■ / □	■ / □	■ / □
Operation mode Online, Offline	■	■	■
Master sets / bookings with 1 MB (approx. value)		5,000 / 10,000	
Master sets / bookings with 3 MB (approx. value)		21,000 / 42,000	
Programmable in TCL, parameterizable in TPI	■	■	■
Realtime-clock with battery, buzzer	■	■	■
Interfaces			
10/100BaseT on pluggable 4 pole screw clamp / RJ45 socket	■ / ■	■ / ■	■ / -
Optional host interface V.24 or RS485 (not simultaneously) ¹	-	-	■
Digital inputs (opto decoupled) / digital outputs (5A)	-	2 / 1	2 / 2
Integrated RFID reader EM 4102/4002, Hitag, Mifare, Legic	□	□	□
Remote readers via LBus	-	1 ²	□ ¹
Control elements and display			
Membrane keyboard with 5 function keys and numeric keypad	■	■	■
Touchscreen with customized keyboard lay-outs	□	□	□
Display 240 x 64 Pixel, black/white	■	■	■
MagicEye (blue, green, red)	■	■	■
Mechanics, power supply, environment			
Tamper contact, strong lock	■	■	■
Current consumption at 230V	250 mA	250 mA	250 mA
Pedestal / cable conduit	□	□	□
Protection: IP30 / with fitting kit IP65	■ / □	■ / □	■ / □
Temperature range 0°C ... +40°C	■	■	■
Heating (for increased temperature range -25°C ... +40°C)	-	-	□
Dimension (H x W x D) in mm		120 x 222 x 295	
Humidity non-condensing		+20%...+90%	
Weight in kg		2,6 kg	
■ Standard □ Option - not available			

¹ in total 2 sockets available, i.e. max. 16 readers
² 1 reader, max. 10 m



PCS Systemtechnik GmbH
 Pfaelzer-Wald-Str.36
 81539 Munich
 phone +49-89-68004-550
 fax +49-89-68004-555
 intus@pcs.com

45136 Essen
 phone +49-201-89416-0

A-1190 Vienna - Austria
 phone +43-1-3670-302

www.pcs.com



Technical specifications subject to change without notice.
 PCS, INTUS, DEXICON, INTUS LBus and "PCS. The terminal people." are registered trademarks of PCS Systemtechnik GmbH. All other brands and products names are trademarks or registered trademarks of the respective companies and organisations.